



# SIM7500\_SIM7600 Series HTTP(S)\_Application Note

LTE Module

## **SIMCom Wireless Solutions Limited**

Building B, SIM Technology Building, No.633, Jinzhong Road  
Changning District, Shanghai P.R. China

Tel: 86-21-31575100

[support@simcom.com](mailto:support@simcom.com)

[www.simcom.com](http://www.simcom.com)

<b>Document Title: :</b>	SIM7500_SIM7600 Series_HTTP(S)_Application Note
<b>Version:</b>	2.00
<b>Date:</b>	2020.8.6
<b>Status:</b>	Released

## GENERAL NOTES

SIMCOM OFFERS THIS INFORMATION AS A SERVICE TO ITS CUSTOMERS, TO SUPPORT APPLICATION AND ENGINEERING EFFORTS THAT USE THE PRODUCTS DESIGNED BY SIMCOM. THE INFORMATION PROVIDED IS BASED UPON REQUIREMENTS SPECIFICALLY PROVIDED TO SIMCOM BY THE CUSTOMERS. SIMCOM HAS NOT UNDERTAKEN ANY INDEPENDENT SEARCH FOR ADDITIONAL RELEVANT INFORMATION, INCLUDING ANY INFORMATION THAT MAY BE IN THE CUSTOMER'S POSSESSION. FURTHERMORE, SYSTEM VALIDATION OF THIS PRODUCT DESIGNED BY SIMCOM WITHIN A LARGER ELECTRONIC SYSTEM REMAINS THE RESPONSIBILITY OF THE CUSTOMER OR THE CUSTOMER'S SYSTEM INTEGRATOR. ALL SPECIFICATIONS SUPPLIED HEREIN ARE SUBJECT TO CHANGE.

## COPYRIGHT

THIS DOCUMENT CONTAINS PROPRIETARY TECHNICAL INFORMATION WHICH IS THE PROPERTY OF SIMCOM WIRELESS SOLUTIONS LIMITED COPYING, TO OTHERS AND USING THIS DOCUMENT, ARE FORBIDDEN WITHOUT EXPRESS AUTHORITY BY SIMCOM. OFFENDERS ARE LIABLE TO THE PAYMENT OF INDEMNIFICATIONS. ALL RIGHTS RESERVED BY SIMCOM IN THE PROPRIETARY TECHNICAL INFORMATION , INCLUDING BUT NOT LIMITED TO REGISTRATION GRANTING OF A PATENT , A UTILITY MODEL OR DESIGN. ALL SPECIFICATION SUPPLIED HEREIN ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.

### **SIMCom Wireless Solutions Limited**

Building B, SIM Technology Building, No.633 Jinzhong Road, Changning District, Shanghai P.R. China

Tel: +86 21 31575100

Email: [simcom@simcom.com](mailto:simcom@simcom.com)

**For more information, please visit:**

<https://www.simcom.com/download/list-863-en.html>

**For technical support, or to report documentation errors, please visit:**

<https://www.simcom.com/ask/> or email to: [support@simcom.com](mailto:support@simcom.com)

**Copyright © 2020 SIMCom Wireless Solutions Limited All Rights Reserved.**

# About Document

## Version History

Version	Date	Owner	What is new
2.00	2020.8.6	Xianxiang Ma	Update the format

SIMCom  
Confidential

# Contents

<b>About Document.....</b>	<b>3</b>
Version History.....	3
<b>Contents.....</b>	<b>4</b>
<b>1. Introduction.....</b>	<b>5</b>
1.1 Purpose of the document.....	5
1.2 Related documents.....	5
1.3 Conventions and abbreviations.....	5
<b>2. HTTP Introduction.....</b>	<b>6</b>
2.1 Characteristic.....	6
2.2 Request Method.....	6
<b>3. AT Commands for HTTP(S).....</b>	<b>8</b>
<b>4. Bearer Configuration.....</b>	<b>9</b>
4.1 PDN Auto-activation.....	9
<b>5. HTTP(S) Samples.....</b>	<b>10</b>
5.1 HTTP Function.....	10
5.1.1 HTTP GET.....	10
5.1.2 Send HTTP POST Request.....	11
5.1.3 Send HTTP HEAD Request.....	12
5.2 Access to HTTPS server.....	13
5.2.1 Send HTTPS GET Request.....	13
5.2.2 Send HTTPS POST Request.....	14
5.2.3 Send HTTPS HEAD Request.....	16
5.2.4 POSTFILE to HTTPS server and read HTTPS response content to a file.....	17

# 1.Introduction

## 1.1 Purpose of the document

Based on module AT command manual, this document will introduce HTTP(S) application process. Developers could understand and develop application quickly and efficiently based on this document.

## 1.2 Related documents

[1] SIM7080 Series\_AT Command Manual

## 1.3 Conventions and abbreviations

In this document, the GSM engines are referred to as following term:

ME (Mobile Equipment);

MS (Mobile Station);

TA (Terminal Adapter);

DCE (Data Communication Equipment) or facsimile DCE (FAX modem, FAX board);

In application, controlling device controls the GSM engine by sending AT Command via its serial interface.

The controlling device at the other end of the serial line is referred to as following term:

TE (Terminal Equipment);

DTE (Data Terminal Equipment) or plainly "the application" which is running on an embedded system;

## 2. HTTP Introduction

HTTP (HyperText Transfer Protocol) is an application layer protocol. When you browse a web page, the browser and the web server will send and receive data on the Internet through the HTTP protocol. HTTP is a stateless protocol based on request and response patterns. That is what we usually call Request/Response.

### 2.1 Characteristic

#### ➤ Support client/server mode;

##### ✧ Simple and fast

When a client requests a service from a server, it only needs to pass the request method and path. Because the HTTP protocol is simple, the program size of the HTTP server is small, and the communication speed is fast.

##### ✧ Flexible

HTTP allows the transfer of any type of data object. The type being transferred is marked by Content-Type;

##### ✧ No connection

No connection means limiting the processing of only one request per link. After the server processes the client's request and receives the customer's response, the server disconnects the link. This way, the transmission time can be saved.

##### ✧ Stateless

The HTTP protocol is a stateless protocol. Stateless means that the protocol has no memory for transaction processing. A lack of state means that if subsequent processing requires the previous information, it must be retransmitted, which may result in an increase in the amount of data transferred per connection. On the other hand, it responds faster when the server does not need previous information.

### 2.2 Request Method

According to the HTTP standard, HTTP requests can use a variety of request methods.

HTTP 1.0 defines three request methods: the GET, POST, and HEAD methods.

HTTP1.1 adds six new request methods: OPTIONS, PUT, PATCH, DELETE, TRACE, and CONNECT

methods.

No	Method	Description
1	GET	Make a request to a specific resource.
2	HEAD	Ask the server for a response that is consistent with the GET request, except that the response body will not be returned. This method can obtain the meta information contained in the response message header without having to transmit the entire response content.
3	POST	Submit data to a specified resource for processing requests (such as submitting a form or uploading a file). The data is included in the request body. POST requests may result in the creation of new resources and/or modifications to existing resources.
4	PUT	Uploads its latest content to a specified resource location.
5	DELETE	Requests the server to delete the resource identified by the Request-URI.
6	CONNECT	H The HTTP/1.1 protocol is reserved for proxy servers that can connect connections to pipes.
7	OPTIONS	Returns the HTTP request method supported by the server for a particular resource. You can also test the functionality of the server by sending a '*' request to the web server.
8	TRACE	Echoes requests received by the server, primarily for testing or diagnostics.
9	PATCH	It is a supplement to the PUT method for local updating of known resources.

The SIM7080 series supports several methods: GET, POST, PUT, PATCH and HEAD.

## 3.AT Commands for HTTP(S)

命令	描述
<b>AT+CSSLCFG</b>	Analysis SSL Configure
<b>AT+HTTPPARA</b>	Set HTTP(S) Parameter
<b>AT+HTTPINIT</b>	start HTTP(S) service
<b>AT+HTTPACTION</b>	HTTP Method Action
<b>AT+HTTPHEAD</b>	Read the HTTP Header Information of Server Response
<b>AT+HTTPREAD</b>	Read the response Information of Server Response
<b>AT+HTTPDATA</b>	You can use AT+HTTPDATA to input data to post when you send a HTTP/HTTPS POST request
<b>AT+HTTPPOSTFILE</b>	send HTTP request in a file via AT+HTTPPOSTFILE command
<b>AT+HTTPREADFILE</b>	Receive HTTP Response Content to a file
<b>AT+HTTPTERM</b>	stop HTTP service.

For detail information, please refer to "SIM7500\_SIM7600 Series\_AT Command Manual".



## 4. Bearer Configuration

Usually module will register PS service automatically.

### 4.1 PDN Auto-activation

```
// Example of PDP Auto-activation.
AT+CPIN? // Check SIM card status
+CPIN: READY

OK
AT+CSQ // Check RF signal
+CSQ: 27,99

OK
AT+CGREG? // Check PS service
+CGREG: 0,1

OK
AT+COPS? // Query Network information, operator and
+COPS: 0,0,"CHN-CT",9 network mode 9, NB-IOT network

OK
AT+CGACT=0,1 // Activating network bearing
OK

AT+CGACT?
+CGACT: 0,1
+CGACT: 1,0
+CGACT: 2,0
+CGACT: 3,0
OK
```

## 5.HTTP(S) Samples

### 5.1 HTTP Function

#### 5.1.1 HTTP GET

// Following commands shows how to send a HTTP GET request to server, and how to read HTTP response.

```
AT+HTTPINIT // start HTTP service, activate PDP context
OK
AT+HTTTPARA="URL","http://opinion.people.com.cn/GB/n1/2018/0815/c1003-30228758.htm" // set the URL which will be accessed, for HTTP, the request URL begins with "HTTP://"
I"
OK
AT+HTTPACTION=0 // send HTTP GET request
OK

+HTTPACTION: 0,200,22505 // 22505 is the length of HTTP response information

AT+HTTPHEAD // read the HTTP response header
+HTTPHEAD: DATA,387

HTTP/1.1 200 OK
Server: nginx
Content-Type: text/html
Connection: close
Date: Thu, 16 Aug 2018 05:13:36 GMT
Powered-By-ChinaCache: MISS from 06053423gG.15
ETag: W/"5b7379f5-57e9"
Last-Modified: Wed, 15 Aug 2018 00:55:17 GMT
Expires: Thu, 16 Aug 2018 05:18:36 GMT
Vary: Accept-Encoding
X-Cache-Hits: 14
```

```

Content-Length: 22505
CC_CACHE: TCP_REFRESH_HIT
Accept-Ranges: bytes

OK
AT+HTTPREAD=0,16           // read 16 bytes form response data
OK                          //data content: <!DOCTYPE html P

+HTTPREAD: DATA,16
<!DOCTYPE html P
+HTTPREAD: 0
AT+HTTPTERM                // stop HTTP Service
OK

```

### 5.1.2 Send HTTP POST Request

```

// HTTP POST and PUT 示例

AT+HTTPINIT                // start HTTP service, activate PDP context
OK
AT+HTTPPARA="URL","http://api.efxnow.com/ //set the URL which will be accessed, for HTTP,
DEMOWebServices2.8/Service.asmx/Echo?" the request URL begins with "HTTP://"
OK
AT+HTTPDATA=18,1000        // send data to post, the length is 18 bytes
DOWNLOAD
Message=helloworld
OK
AT+HTTPACTION=1            // send HTTP POST request
OK                          // 30 is the length of HTTP response information

+HTTPACTION: 1,500,30

+HTTP_PEER_CLOSED
AT+HTTPHEAD                // read the HTTP response header
OK
+HTTPHEAD: DATA,258
HTTP/1.1 500 Internal Server Error
Cache-Control: private
Content-Type: text/plain; charset=utf-8
Server: Microsoft-IIS/7.0

```

```
X-AspNet-Version: 2.0.50727
X-Powered-By: ASP.NET
Date: Mon, 20 Aug 2018 04:18:58 GMT
Connection: close
Content-Length: 30

OK
AT+HTTPREAD=0,30
OK
// read the response information of HTTP server,
the length to read is 30 bytes

+HTTPREAD: DATA,30
Request format is invalid: .

+HTTPREAD: 0
AT+HTTPTERM
OK
// stop HTTP Service
```

### 5.1.3 Send HTTP HEAD Request

```
// HTTP HEAD 示例

AT+HTTPINIT
OK
// start HTTP service, activate PDP context

AT+HTTPPARA="URL","http://opinion.people.
com.cn/GB/n1/2018/0815/c1003-30228758.html
"
OK
// set the URL which will be accessed, for HTTP,
the request URL begins with "HTTP:/"

AT+HTTPACTION=2
OK
//send a HEAD request to server to only get
header of HTTP response

+HTTPACTION: 2,200,387

+HTTP_PEER_CLOSED

AT+HTTPHEAD
OK
// send HTTP POST request

// 30 is the length of HTTP response information

+HTTPACTION: 1,500,30

+HTTP_PEER_CLOSED
```

```
AT+HTTPHEAD                                     // read the HTTP response header
OK
+HTTPHEAD: DATA,387
HTTP/1.1 200 OK
Server: nginx
Content-Type: text/html
Connection: close
Vary: Accept-Encoding
Powered-By-ChinaCache:      MISS      from
06053423gG.15
ETag: W/"5b7379f5-57e9"
Last-Modified: Wed, 15 Aug 2018 00:55:17 GMT
Content-Length: 22505
X-Cache-Hits: 14
Date: Thu, 16 Aug 2018 10:58:00 GMT
Expires: Thu, 16 Aug 2018 11:03:00 GMT
CC_CACHE: TCP_REFRESH_HIT
Accept-Ranges: bytes

OK
AT+HTTPREAD=0,30
OK

+HTTPREAD: DATA,30
Request format is invalid: .

+HTTPREAD: 0
AT+HTTPTERM                                     // stop HTTP Service
OK
```

## 5.2 Access to HTTPS server

### 5.2.1 Send HTTPS GET Request

```
//HTTPS GET

AT+HTTPINIT                                     //start HTTP service, activate PDP context
OK
```

```
AT+HTTTPARA="URL","https://ss0.bdstatic.co
m/5aV1bjqh_Q23odCf/static/mancard/css/card_
min_dee38e45.css" // set the URL which will be accessed, for HTTPS,
// the request URL begins with "HTTPS://"
OK
AT+HTTTPACTION=0 // send HTTPS GET request
OK

+HTTTPACTION: 0,200,52060
AT+HTTTPHEAD // read HTTPS response header
+HTTTPHEAD: DATA,390 //390 is the length of HTTPS response header

HTTP/1.1 200 OK
Server: bfe/1.0.8.13-sslpool-patch
Date: Thu, 16 Aug 2018 11:38:08 GMT
Content-Type: text/css
Content-Length: 52060
Connection: close
ETag: "5a323f72-cb5c"
Last-Modified: Thu, 14 Dec 2017 09:08:02 GMT
Expires: Sat, 18 Aug 2018 09:50:53 GMT
Age: 2425635
Accept-Ranges: bytes
Cache-Control: max-age=2592000
Vary: Accept-Encoding
Ohc-Response-Time: 1 0 0 0 0

OK
AT+HTTTPREAD=0,24
OK

+HTTTPREAD: DATA,24
.s-cardsetting{position:
+HTTTPREAD: 0
AT+HTTTPTERM // stop HTTP Service
OK
```

## 5.2.2 Send HTTPS POST Request

```
//HTTPS POST
```

<p><b>AT+HTTTPARA="URL","https://pv.csdn.net/csdnbi"</b></p> <p>OK</p>	<p>// set the URL which will be accessed, for HTTPS, the request URL begins with "HTTPS://"</p>
<p><b>AT+HTTPINIT</b></p> <p>OK</p> <p><b>AT+HTTPDATA=465,1000</b></p> <p>DOWNLOAD</p> <pre>[{"headers":{"component":"enterprise","datatype":"track","version":"v1"},"body":{"re":{"uid=merry1996&amp;ref=https%3A%2F%2Fpassport.csdn.net%2Faccount%2Fverify%3Bjsessionid%3D7895A57BC64CE8616517F558940FD913.tomcat2&amp;pid=www&amp;mod=&amp;con=&amp;ck=-&amp;curl=https%3A%2F%2Fwww.csdn.net%2F&amp;session_id=10_1534696351647.160829&amp;tos=12&amp;referrer=https%3A%2F%2Fpassport.csdn.net%2Faccount%2Fverify%3Bjsessionid%3D7895A57BC64CE8616517F558940FD913.tomcat2&amp;user_name=merry1996&amp;type=pv\"}}}]</pre> <p>OK</p>	<p>///start HTTP service, activate PDP context</p> <p>// send data to post, the length is 465 bytes</p>
<p><b>AT+HTTPACTION=1</b></p> <p>OK</p> <p>+HTTPACTION: 1,200,2</p> <p>+HTTP_PEER_CLOSED</p> <p><b>AT+HTTPHEAD</b></p> <p>OK</p> <p>+HTTPHEAD: DATA,377</p> <p>HTTP/1.1 200 OK</p> <p>Server: openresty</p> <p>Date: Mon, 20 Aug 2018 03:20:30 GMT</p> <p>Content-Type: application/octet-stream</p> <p>Connection: close</p> <p>Set-Cookie:</p> <p>uuid_tt_dd=10_37481894210-1534735230305-445993; Expires=Thu, 01 Jan 2025 00:00:00 GMT; Path=/; Domain=.csdn.net;</p> <p>Set-Cookie:</p> <p>dc_session_id=10_1534735230305.501284; Expires=Thu, 01 Jan 2025 00:00:00 GMT; Path=/; Domain=.csdn.net;</p> <p>OK</p>	<p>//send HTTPS post request</p> <p>//2 is the length of HTTPS response information</p> <p>//read the HTTPS response header</p>

<b>AT+HTTPTERM</b>	// stop HTTP Service
OK	

### 5.2.3 Send HTTPS HEAD Request

```
// HTTPS HEAD

AT+HTTPINIT //start HTTP service, activate PDP context
OK

AT+HTTPPARA="URL","https://ss0.bdstatic.com/5aV1bjqh_Q23odCf/static/mancard/css/card_min_dee38e45.css" //set the URL which will be accessed, for HTTPS,
//the request URL begins with "HTTPS://"
OK

AT+HTTPACTION=2 // send HTTPS HEAD request
OK

+HTTPACTION: 2,200,390

+HTTP_PEER_CLOSED
AT+HTTPHEAD // read HTTPS response header
+HTTPHEAD: DATA,390

HTTP/1.1 200 OK
Server: bfe/1.0.8.13-sslpool-patch
Date: Thu, 16 Aug 2018 11:46:22 GMT
Content-Type: text/css
Content-Length: 52060
Connection: close
ETag: "5a323f72-cb5c"
Last-Modified: Thu, 14 Dec 2017 09:08:02 GMT
Expires: Sat, 18 Aug 2018 09:50:53 GMT
Age: 2426129
Accept-Ranges: bytes
Cache-Control: max-age=2592000
Vary: Accept-Encoding
Ohc-Response-Time: 1 0 0 0 0

OK
AT+HTTPTERM //stop HTTP Service
OK
```



## 5.2.4 POSTFILE to HTTPS server and read HTTPS response content to a file

```
// HTTPS POST/PUT

AT+HTTPIPINIT // start HTTP service, activate PDP context
OK
AT+HTTTPARA="URL","https://www.baidu.com" //access server and send file getbaidu.txt to server
OK
AT+HTTPPOSTFILE="getbaidu.txt",1,0 // access server and send file getbaidu.txt to
OK server

+HTTPPOSTFILE: 0,200,14615

+HTTP_PEER_CLOSED
AT+HTTPHEAD // read the HTTP server response header
+HTTPHEAD: DATA,773 information.
HTTP/1.1 200 OK
Accept-Ranges: bytes
Cache-Control: no-cache
Connection: Keep-Alive
Content-Length: 14615
Content-Type: text/html
Date: Thu, 13 Sep 2018 05:14:30 GMT
Etag: "5b8641dc-3917"
Last-Modified: Wed, 29 Aug 2018 06:49:00 GMT
P3p: CP=" OTI DSP COR IVA OUR IND COM "
Pragma: no-cache
Server: BWS/1.1
Set-Cookie:
BAIDUID=A374BCFD28DFEEAF0BA0C4EEAC
77B0B0:FG=1; expires=Thu, 31-Dec-37
23:55:55 GMT; max-age=2147483647; path=/;
domain=.baidu.com
Set-Cookie:
BIDUPSID=A374BCFD28DFEEAF0BA0C4EEA
C77B0B0; expires=Thu, 31-Dec-37 23:55:55
GMT; max-age=2147483647; path=/;
domain=.baidu.com
Set-Cookie: PSTM=1536815670; expires=Thu,
31-Dec-37 23:55:55 GMT;
max-age=2147483647; path=/;
domain=.baidu.com
```

Vary: Accept-Encoding

X-Ua-Compatible: IE=Edge,chrome=1

OK

**AT+HTTPTERM**

// stop HTTPS Service

OK

SIMCom  
Confidential